

DEC 1951

CONFIDENTIAL

25X1

CENTRAL INTELLIGENCE AGENCY
INFORMATION REPORT

COUNTRY China

REPORT NO. [REDACTED]

25X1A

SUBJECT Shanghai; Location of Shanghai Power Company Sub-
Stations/Transmission and Distribution Cables in
Operation/Route Length of Overhead Lines in Operation

PLACE ACQUIRED [REDACTED]

DATE ACQUIRED [REDACTED]

DATE (OF INFO. [REDACTED])

25X1A

RESPONSIVE TO	
1	2
[REDACTED]	
[REDACTED]	
[REDACTED]	
[REDACTED]	
[REDACTED]	
[REDACTED]	
[REDACTED]	
[REDACTED]	

25X1A

DATE DISTR. 8 June 1954

NO. OF PAGES 3

NO. OF ENCLS.

SUPP. TO
REPORT NO.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE
OF THE UNITED STATES, WITHIN THE MEANING OF TITLE 18, SECTIONS 793
AND 794, OF THE U.S. CODE, AS AMENDED. ITS TRANSMISSION OR REVE-
LATION OF ITS CONTENTS TO OR RECEIPT BY AN UNAUTHORIZED PERSON IS
PROHIBITED BY LAW. THE INFORMATION OF THIS REPORT IS UNCLASSIFIED.

THIS IS UNEVALUATED INFORMATION

25X1X

Location of Substations
and source of supply22000 Volt Distribution

Yangchow Substation - Two miles west of the generating plant
supplied by two .2 sq inch and
three .15 sq in 22,000 volt cables

Farson Road Substation-Two miles west of Yangchow. Supplied
by six .15 sq inch and two .2 sq inch
cables from Riverside

Connaught Road Sub-
station - Three miles west of Farson Road.
Supplied by three .2 sq inch cables
from Riverside.

Tonquin Substation - One mile due north of Connaught Substation.
Supplied by five .2 sq inch and two .15 sq
inch cables from Riverside and two .15 sq
inch cables from Farson Road.

Robison Substation - About 1 1/2 miles from both Connaught and
Tonquin Substations, being located at the
third point of an equilateral triangle
joining the three substations. Thus it is
located about one mile farther west than
Tonquin and Connaught.
Supplied by three .2 sq inch cables from
Riverside and two .2 sq inch cables from
Tonquin.

Brennan Substation - Located two miles west of Robison, outside
the Settlement limits.
Supplied by two .15 sq inch cables from
Robison.

CONFIDENTIAL

25X1

DISTRIBUTION	STATE	ARMY	NAVY	AIR	FBI	ORR-Ev		
--------------	-------	------	------	-----	-----	--------	--	--

This report is for the use within the USA of the Intelligence components of the Departments or
Agencies indicated above. It is not to be transmitted overseas without the concurrence of the
originating office through the Assistant Director of the Office of Collection and Dissemination, CIA.

CONFIDENTIAL

-2-

25X1

25X1A

Both Yangchow and Connaught Substations are fed directly from Riverside Plant without any 22 kv interconnection with the other substations on the system. Fearon Road, Tonquin and Robison are interconnected by tie feeders and Breuners is supplied radially from Robison. However, the 22,000 volt busses at Fearon, Tonquin and Robison are not interconnected for operating purposes.

6000 Volt Distribution

It is the custom to supply a minor switching point from a major supply substation and to regulate all or part of the substation bus supplying the regulated feeders. Except for outlying sections each of these 6600 volt substations is supplied by a separate feeder.

Transmission and Distribution Cables in Operation (Miles)

System Voltage	At end of 1938		Net Increase for 1939	At end of 1939		Distribution only
				sub-Totals	Grand Total (A + B)	
			Miles			
23,000	In Operation (A)	240.0604	5.3143	245.3747	246.0897	
	Not in Operation (B)	0.7150	-	0.7150		
6,600	In Operation (A)	182.2807	5.5596	182.8403	190.9207	
	Not in Operation (B)	8.0585	.0219	8.0804		
380	In Operation (A)	48.2991	.1409	48.4400	50.2218	241.1425
	Not in Operation (B)	1.7693	.0125	1.7818		
Total Length of Power Cables		481.1830	6.0492	487.2322	487.2322	
Telephone and Pilot	In Operation (A)	155.6835	5.4981	161.1816		164.2320
	Not in Operation (B)	3.0504	-	3.0504		

Cables "not in operation" are pot ended buried cables.

Underground Cables In Operation

Voltage, Type, Size and Length (Miles)

System voltage	Type of Cable	Armour	Size Sq Inch	Length (Miles)
23,000	Belted, solid	P I L C & D B T	.1	0.10
"	" , split	"	.15	70.01
"	"	"	.20	71.44
"	H S L, solid	P I L C & S W A	.1	0.75

CONFIDENTIAL

25X1

CONFIDENTIAL

-3-

25X1

25X1A

System voltage	Type of Cable	Armour	Size Sq Inch	Length (Miles)
23,000	H S L, solid	P I L C & S W A	.2	61.28
"	" split	"	.2	24.05
"	H solid	P I L C	.2	3.90
"	H solid	P I L C & D S T	.2	2.54
"	H solid	"	.4	9.24
"	H solid	P I L C	.4	2.35
"	Miscellaneous	-	-	0.43 246.09
6,000	Belted, solid	P I L C & D S T	.025	30.70
"	"	"	.05	1.94
"	"	"	.06	1.47
"	"	"	.1	20.19
"	"	"	.15	43.07
"	"	"	.2	34.04
"	"	"	.2	23.87
"	"	"	.3	31.46
"	Miscellaneous	-	-	4.18 190.92
380	Belted, solid	P I L C & D S T	.0084	3.06
"	"	P I L C	.0084	2.76
"	"	P I L C & D S T	.028	1.51
"	"	"	.05	1.15
"	"	"	.075	1.92
"	"	"	.15	0.67
"	"	"	.25	6.41
"	"	"	.3	4.21
"	"	P I L C & D S T	.4	27.67
"	Miscellaneous	-	-	0.86 50.22
Pilot	Belted, solid	-	.0045	13.25
"	"	-	.0084	88.74
"	"	-	(6 pair x .0084)	10.06
			(4 pair	112.05

Route Length of Overhead Lines in OperationMiles

	In Operation at end of 1938	Erected During 1939	Dismantled During 1939	Net Increase in 1939	Lines in Operation at end of 1939
6,600 volt feeders and distributors	19.1767	3.5751	0.3153	3.2598	22.4365
386/220-v Road Mains	127.2232	2.2793	0.9508	1.3285	128.5517)
380/220v-Alleyway mains	351.8638	14.0941	6.6360	7.4581	359.3219)
Total Distribution Lines	498.2637	19.9485	7.9021	12.0464	510.3101
Street Lighting	560.3354	15.8147	6.7547	9.0600	569.3954
D C Circuits	5.8541	-	-	-	5.8541
Auto Telephone	0.9711	0.0352	-	0.0352	1.0063

-end-

735.912
735.911581L
581L

CONFIDENTIAL

25X1